



REPUBLIC OF NAMIBIA  
KUNENE REGIONAL COUNCIL  
DIRECTORATE: EDUCATION, ARTS & CULTURE



# Request for Quotations For Works

## Construction of new ablution blocks

Construction of new ablution blocks at Versteende Woud  
Primary School, Otjitoko Primary School)

Procurement Reference No: W/RFQ/KRC:DoEAC-21/2021

Kunene Regional Council  
P/Bag 502  
Opuwo  
Namibia

TEL: 065 273950  
pmu@kunenerc.gov.na



Name of bidder: \_\_\_\_\_

Contact Number of Bidder: \_\_\_\_\_

Email Address of Bidder: \_\_\_\_\_

Signature of Bidder: \_\_\_\_\_

Bid total amount: N\$ \_\_\_\_\_



**REPUBLIC OF NAMIBIA**  
**KUNENE REGIONAL COUNCIL**  
**DIRECTORATE: EDUCATION, ARTS & CULTURE**



**Letter of Invitation**

**24<sup>th</sup> February 2021**

**To:** .....  
 .....  
 .....  
 .....

**Procurement Reference Number: W/RFQ/KRC:DoEAC-21/2021**

Dear Sirs,

**Request for Quotations for construction of new ablution block for Directorate of Education, Arts and Culture: Kunene Regional Council**

Any resulting contract shall be subject to the terms and conditions referred to in the document.

Queries, if any, should be addressed to Ms Sendra Nakale 065-273950 or Simeon Kariko 0811482090.

Please prepare and submit your quotation in accordance with the instructions given or inform the undersigned if you will not be submitting a quotation.

Yours faithfully,

  
 \_\_\_\_\_

**J.E. JANTZE**

**ACTING CHIEF REGIONAL OFFICER**



## **SECTION I: INSTRUCTIONS TO BIDDERS**

### **1. Rights of Public Entity**

The Kunene Regional Council: Directorate of Education, Arts and Culture reserves the right:

- (a) to split the contract as per the lowest evaluated cost per lot; and
- (b) to accept or reject any quotation or to cancel the quotation process and reject all quotations at any time prior to contract award.

### **2. Preparation of Quotations**

You are requested to quote for the works mentioned in Section III, by completing, signing and returning:

- (a) the Quotation Letter in Section II with its annex for Bid Securing Declaration, where applicable;
- (b) the Priced Activity Schedule in Section IV;
- (c) the Specifications and Compliance Sheet in Section V; and
- (d) any other attachment as deemed appropriate

You are advised to carefully read the complete Request for Quotations document, including the Special Conditions of Contract in Section VII, before preparing your Quotation. The standard forms in this document may be retyped for completion but the Bidder is responsible for their accurate reproduction.

### **3. Validity of Quotations**

The quotation validity period shall be 180 days from the date of bid submission deadline.

### **4. Eligibility Criteria**

To be eligible to participate in this Quotation exercise, you should:

- (a) have a certified valid copy of company Registration Certificate;
- (b) have a certified valid copy of good Standing Tax Certificate;
- (c) have a certified valid copy of good Standing Social Security Certificate;
- (d) have a valid certified copy of Affirmative Action Compliance Certificate, proof from Employment Equity Commissioner that bidder is not a relevant employer, or exemption issued in terms of Section 42 of the Affirmative Action Act, 1998;
- (e) have a valid certified copy of certificate indicating SME Status (for Bids reserved for SMEs);
- (f) Submit signed bid securing declaration
- (g) Attach proof of confirmation of account from a Namibian Banking institution
- (h) Bidders place of principal business must be in Kunene Region. (Attach the confirmation letter from the regional Councillor responsible for your constituency).
- (i) Attached TWO (2) Purchase order or completion certificate of completed works with the same complexity.

(j) Bidders are allowed to bid for all lots, but only be awarded on lot for this bid.

## **5. Bid Securing Declaration**

Bidders are required to subscribe to a Bid Securing Declaration for this procurement process.

## **6. Works Completion Period**

The completion period for works shall be 60 days after acceptance and issue of Purchase Order. Deviation in completion period shall not be accepted.

## **7. Sealing and Marking of Quotations**

Quotations should be sealed in a single envelope, clearly marked with the Procurement Reference Number, addressed to the Public Entity with the Bidder's name at the back of the envelope.

## **8. Submission of Quotations**

Quotations should be deposited in the Quotation/Bid Box located at P/Bag 502 Opuwo Kunene Regional Council, Mbumbijazo Muharukua Street, Opuwo or forwarded by fax 065-273077, not later than **03 March 2021** at 11h00 AM.. **Quotations by post or hand delivered should reach Kunene Regional Council Mbumbijazo Muharukua Street, P/Bag 502 Opuwo by the same date and time at latest 11h00. Late quotations will be rejected.** Quotations received by e-mail or fax will not be considered.

## **9. Opening of Quotations**

Quotations will be opened internally by the Public Entity immediately after the closing time referred to in section 8 above. A record of the Quotation Opening stating the name of the bidders, the amount quoted, the presence or absence of a Bid Security/Bid Securing Declaration, will be posted on the website of the Public Entity and available to any bidder on request within three working days of the Opening.

## **10. Evaluation of Quotations**

The Public Entity shall have the right to request for clarifications in writing during evaluation. Offers that are substantially responsive shall be compared on the basis of evaluated cost, subject to Margin of Preference where applicable, to determine the lowest evaluated quotation.

## **11. Technical Compliance**

The Specifications and Compliance Sheet details the minimum specifications of the works to be carried out. The specifications have to be met, but no credit will be given for exceeding the specifications.

## **12. Prices and Currency of Payment**

Prices for the execution of works shall be fixed in Namibian Dollars as quoted.

Quotations shall cover all costs of labour, materials, equipment, overheads, profits and all associated costs for performing the works, and shall include all duties. The whole cost of

performing the works shall be included in the items stated, and the cost of any incidental works shall be deemed to be included in the prices quoted.

### **13. Margin of Preference**

13.1 The applicable margins of preference and their application methodology are as follows:

N/A

13.2 Bidders applying for the Margin of Preference shall submit, **upon request**, evidence of:

N/A

### **14. Award of Contract**

The Bidder having submitted the lowest evaluated responsive quotation that is 0% above and not less than 15% below the engineer's estimates, with market related rates and qualified to perform the works shall be selected for award of contract. Award of contract shall be by issue of a Purchase Order/Letter of Acceptance in accordance with terms and conditions contained in Section VI: Contract Agreement and General Conditions of Contract.

### **15. Performance Security**

None

### **16. Notification of Award and Debriefing**

The Public Entity shall after award of contract promptly inform all unsuccessful bidders in writing of the name and address of the successful bidder and the contract amount and post a notice of award on its website within 7 days. Furthermore, the Public Entity shall attend to all requests for debriefing made in writing within seven days of the unsuccessful bidders being informed of the award.

## SECTION II: QUOTATION LETTER

(to be completed by Bidders)

*[Complete this form with all the requested details and submit it as the first page of your quotation with the Priced Activity Schedule and documents requested above. A signature and authorisation on this form will confirm that the terms and conditions of the RFQ prevail over any attachments. **If your quotation is not authorised, it will be rejected***

Quotation addressed to:	
Procurement Reference Number:	
Subject matter of Procurement:	

We offer to execute the Works detailed in the Statement of Requirements, in accordance with the terms and conditions stated in your Request for Sealed Quotations referenced above.

We confirm that we are eligible to participate in this Quotation exercise and meet the eligibility criteria specified in Section I: Instructions to Bidders

We undertake to abide by the Conduct of Bidders and Suppliers as provided under the Public Procurement Act during the procurement process and the execution of any resulting contract.

We have read and understood the content of the *Bid Security / Bid Securing Declaration* (BSD) attached hereto and subscribe fully to the terms and conditions contained therein. We further understand that this subscription shall be construed as a Bid Securing Declaration which could lead to disqualification on the grounds mentioned in the BSD. *[Public Entity shall delete this paragraph in case no security is required or re-write the paragraph accordingly in case a Bid Security is requested]*.

The validity period of our Quotation is \_\_\_\_\_ days from the date of the bid submission deadline.

We confirm that the prices quoted in the Priced Activity Schedule are fixed and firm and will not be subject to revision or variation, if we are awarded the contract **prior to the expiry** date of the quotation validity.

Works will commence within \_\_\_\_\_ days from date of issue of Purchase Order/ Letter of Acceptance.

Works will be completed within \_\_\_\_\_ days from date of issue of Purchase Order/Letter of acceptance.

We declare that we “qualify/do not qualify” for Margin of Preference applicable to Small and Medium enterprises and shall upon request submit documentary evidence in this respect. *[Bidder to strike out as appropriate]*

### Quotation Authorised by:

Name of Bidder		Company's Address and seal	
Contact Person			
Name of Person Authorising the Quotation:		Position:	Signature:
Date		Phone No./E-mail	

**BID SECURING DECLARATION**  
**(Section 45 of Act)**  
**(Regulation 37(5) and 56(2))**

**Date:** .....

**Procurement Ref No.:** .....

**To:**

.....  
 .....[insert  
*complete name of Public entity and address*]

I/We\* understand that in terms of section 45 of the Act a public entity must include in the bidding document the requirement for a declaration as an alternative form of bid security.

I/We\* accept that under section 45 of the Act, I/we\* may be suspended or disqualified in the event of

- (a) **a modification or withdrawal of a bid after the deadline for submission of bids during the period of validity;**
- (b) **refusal by a bidder to accept a correction of an error appearing on the face of a bid;**
- (c) **failure to sign a procurement contract in accordance with the terms and conditions set forth in the bidding document, should I/We\* be successful bidder; or**
- (d) **failure to provide security for the performance of the procurement contract if required to do so by the bidding document.**

I/We\* understand this bid securing declaration ceases to be valid if I am/We are\* not the successful Bidder

Signed: .....  
 [insert signature of person whose name and capacity are shown]

Capacity of:  
 [indicate legal capacity of person(s) signing the Bid Securing Declaration]

Name: .....  
 [insert complete name of person signing the Bid Securing Declaration]

Duly authorized to sign the bid for and on behalf of: [insert complete name of Bidder]

Dated on \_\_\_\_\_ day of \_\_\_\_\_  
 [insert date of signing]

Corporate Seal (where appropriate)

[Note\*: In case of a joint venture, the bid securing declaration must be in the name of all partners to the joint venture that submits the bid.]

**\*delete if not applicable / appropriate**



## Republic Of Namibia

### Ministry of Labour, Industrial Relations and Employment Creation

Written undertaking in terms of section 138 of the Labour Act, 2015 and section 50(2) (D) of the Public Procurement Act, 2015

#### 1. EMPLOYERS DETAILS

Company Trade Name:.....

Registration Number :.....

Vat Number: .....

Industry/Sector: .....

Place of Business:.....

Physical Address:.....

Tell No.:.....

Fax No.:.....

Email Address:.....

Postal Address:.....

Full name of Owner/Accounting Officer:.....

.....

Email Address :.....



## 2. PROCUREMENT DETAILS

Procurement Reference No : .....

Procurement Description: .....

.....

Anticipated Contract Duration: .....

Location where work will be done, good/services will be delivered: .....

.....

## 3. UNDERTAKING

I ..... *[insert full name]*, owner/representative

of ..... *[insert full name of company]*

hereby undertake in writing that my company will at all relevant times comply fully with the relevant provisions of the Labour Act and the Terms and Conditions of Collective Agreements as applicable.

I am fully aware that failure to abide to such shall lead to the action as stipulated in section 138 of the labour Act, 2007, which include but not limited to the cancellation of the contract/licence/grant/permit or concession.

**Signature:** .....

**Date:** .....

**Seal:** .....

*Please take note:*

1. *A labour inspector may conduct unannounced inspections to assess the level of compliance*
2. *This undertaking must be displayed at the workplace where it will be readily accessible and visible by the employees rendering service(s) in relations to the goods and services being procured under this contract.*

### **SECTION III: STATEMENT OF REQUIREMENTS**

#### **A. SCOPE OF WORKS, SPECIFICATIONS AND PERFORMANCE REQUIREMENTS**

**Construction of Ablution Block in accordance with the specification provided under Section IV**

#### **B. DRAWINGS**

**SEE ATTACHED DRAWINGS**

**NB! NOTE THAT ALL TOILET POTS MUST BE OF WHITE CERAMIC AND NOT STAINLESS STEEL AS PER ATTACHED CONSTRUCTION PLAN**

**Insert here a list of Drawings. The actual Drawings, including site plans, should be attached to this section or annexed in a separate folder.**

**LOT 1: VERSTEENDE WOOD PRIMARY SCHOOL****EARTH WORK**

<b>Item No</b>	<b>Brief Description of Services</b>	<b>Quantity</b>	<b>Unit Measure</b>	<b>Unit Price</b>	<b>Total Price</b>
<b>A*</b>	<b>B*</b>	<b>C*</b>	<b>D*</b>	<b>E</b>	<b>F</b>
<b>Bulk excavations, fillings, etc</b>					
1.	Extra over bulk excavation in earth for excavation in Soft rock (the use of jack hammers is necessary.	15.00	m <sup>3</sup>		
2.	Extra over bulk excavation in earth for excavation in Hard rocks (blasting is necessary	15.00	m <sup>3</sup>		
3.	Extra over all excavations for carting Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor	50.00	m <sup>3</sup>		
<b>Ordinary excavations, fillings</b>					
4.	Earth filling obtained from the excavations and/or prescribed stock piles on site compacted to 93% mod AASHTO density Backfilling to trenches, holes, etc.	13.00	m <sup>3</sup>		
5.	Earth filling supplied by the contractors to 93% mod AASHTO density Under floors, steps, pavings, etc.	75.00	m <sup>3</sup>		
6.	Compaction of filling Extra over all filling compacted to 93% mod AASHTO fir compacting to 98% AASHTO	78.00	m <sup>3</sup>		
7.	Coarse river and sand filling supplied by the contractor Backfilling behind retaining walls	26.00	m <sup>3</sup>		
8.	Soil poisoning. Soil insecticide under floors, paving, etc. including forming and poisoning shallow furrows and ramming	84.00	m <sup>2</sup>		
9.	Soil poisoning .Soil insecticide to bottoms of trenches, holes, etc.	65.00	m2		
<b>Concrete, Formwork and Reinforcement</b>					
10.	<u>Concrete work (unreinforced and reinforced) 15Mpa/ 19mm</u>	5.00	m <sup>3</sup>		

	concrete .Surface beds, aprons, pavings, ramps, etc. cast in panels				
11.	25Mpa/ 19mm concrete Footings, bases and ground beams	10.00	m <sup>3</sup>		
12.	25Mpa/ 19mm concrete Surface beds, aprons, pavings, ramps, etc. cast in panels	12.00	m <sup>3</sup>		
<b>Masonry: Brickwork in foundation</b>					
13.	Brickwork of 7MPa cement bricks in Class 1 mortar. Half brick wall	15.00	m <sup>2</sup>		
14.	Brickwork of 14MPa cement bricks in class 1 mortar. One brick wall	30.00	m <sup>2</sup>		
<b>Brickwork in superstructures</b>					
15.	Brickwork of 7MPa cement bricks in Class 1 mortar. Half brick wall	40.00	m <sup>2</sup>		
16.	Brickwork of 7MPa cement bricks in Class 1 mortar. One brick wall	130.00	m <sup>2</sup>		
<b>Brickwork sundries</b>					
17.	Galvanised hoop iron ties.1.6mm Galvanised hoop iron tie 30mm wide and 750 mm girth build into brickwork and wrapped around and spiked to wall plate	6.00	No		
18.	Prestressed prefabricated lintels 105 X 75mm Lintels in lengths not exceeding 3m	12.00	m		
<b>Waterproofing: Damp-proofing of walls and floors</b>					
19.	One layer of approved 375 micron embossed damp proof course. In walls (110mm and 22mm wide)	60.00	m <sup>2</sup>		
20.	One layer of approved 250 micron under surface bed type waterproof sheeting sealed at laps with pressure sensitive tap Under surface beds, apron. etc	78.00	m <sup>2</sup>		

<b>Roof coverings: 0.5mm Galvanised corrugated iron (Z275 spelter) roof sheeting with 0.6mm galvanised sheet steel accessories fixed in strict accordance with the manufacturer's instructions</b>					
21.	0.58mm "IBR" profile full hard galvanised (Z275 spelter) steel troughed roofing with 0.8mm galvanised sheet steel accessories fixed in strict accordance with the manufacturer's instruction. Roof sheeting in single lengths sheet	80.00	m <sup>2</sup>		
22.	0.5mm 'IBR 686' Aluzinc profile steel toughed roofing and all accessories fixed in strict accordance with the manufacturer's Instructions with fastening brackets and fixing specifications for areas of strong winds according to : Clotan Steel" with all exposed roofing screws, bolts, etc. sealed with a suitable acrylic waterproofing system .Ridge capping	12.00	m		
<b>Roof and wall insulation</b>					
23.	4mm 'Alucushion" bubble oil insulation with aluminium foil one side and white polyethylene other side or other equal and approved. Insulation laid taut over purlins and fixed concurrent with roof covering and vertical cladding including galvanise steel straining wires.	72.00	m <sup>2</sup>		
<b>Carpentry Work: Flush Doors</b>					
24.	40mm Semi-solid flush doors with hardboard covering both sides and concealed hardwood edge strips. Door size 813 X 2032mm high	7.00	No		
<b>Ceilings and partitions: Metal ceilings</b>					
25.	0.5mm IBR profile full hard galvanised steel troughed roofing with 0.8mm galvanised sheet	78.00	m <sup>2</sup>		

	steel accessories fixed in strict accordance with the manufacturer's instructions. Ceilings in single length sheets fixed horizontally to underside of steel purlins				
26.	0.5mm IBR profile full hard galvanised steel troughed roofing with 0.8mm galvanised sheet steel accessories fixed in strict accordance with the manufacturer's instructions .Extra over ceiling for trap door sixe 600x600mm, the opening formed of 40x40x0.8mm galvanised sheet metal angle from all round mitred and pop-riveted to profiled metal ceiling and 50 x 50 x 3mm mild steel angle frame all round mitred and welded together and to steel brandering, the trap door formed of IBR profiled metal sheeting with 40 x 40 x 0.8mm galvanised sheet metal angle frame all round mitred and pop-riveted to profiled metal ceiling	1.00	No		
<b>Floor Covering, wall linings etc. <u>Floor coverings</u></b>					
27.	300 x 300 x 2mm fully flexible vinyl tiles to patterns in differing colours fixed with and adhesive recommended by and laid in strict accordance with the manufacturer's instructions. Floors	87.00	m <sup>2</sup>		
<b>Ironmongery</b>					
28.	Door and window sundries .Silver anodised aluminium door stop with rubber buffer fixed to floor	12.00	No		
<b>Structural steelwork: Steel trusses etc.</b>					
29.	Welded roof trussers of angle section hollow section rafters, rails, struts, braes, cleats etc. and flat section barer, gust and connection plates bolted to concrete. Truss exceeding 6m and not exceeding 8m span	550.00	kg		

30.	Base plates, angles and bolts to trusses .Base or anchor plates	55.00	kg		
31.	Base plates, angles and bolts to trusses.12mm U-shaped anchor bolt 750mm girth cast into top of concrete	12.00	No		
<b>Purlins, girts, bracing etc.</b>					
32.	Purlins and braces bolted to steel Lipped channel section purlins	432.00	kg		
33.	Purlins and braces bolted to steel Lipped channel section ceiling rails	410.00	kg		
<b>Metal work :Mild steel windows and doors</b>					
34.	Residential type window with horizontal bars with solid brass or chromium plated fittings and fitted with and including type NBP33 burglar bars to the opening sections only. Window type C2H size 1022 x 654mm high	6.00	No		
<b>Pressed steel door frames</b>					
35.	1.2mm Double rebated frames suitable for half brick walls Frame for door size 813 x 2032mm high	7.00	No		
<b>Pressed steel combination doors and frames</b>					
36.	Combination single panel chawl type doors with 14.2mm rebated door rebate door frames to suit one brick walls .Frame with door size 813 x 2032mm high with palatch	3.00	No		
37.	Combination single panel chawl type doors with 14.2mm rebated door rebate door frames to suit one brick walls .Frame with door size 813 x 2032mm high with three level lockset and chromium plated furniture.	2.00	No		
<b>Plastering: External Plaster</b>					

38.	One coat cement plaster wood floated smooth on brick work to: Walls	120.00	m <sup>2</sup>		
<b>Internal plaster</b>					
39.	One coat compo plaster steel trowelled smooth on brickwork to: Walls	180.00	m <sup>2</sup>		
<b>Dividing strip, water bars, cornee protectors, etc</b>					
40.	Mild steel. 50 x 50 x 5mm angle section edge protector in lengths with and including 2 x 25mm flat section bent lugs each 200mm girth welded on at maximum 300mm centres including embedding in concrete	19.00	m		
<b>Tiling :Wall tiling</b>					
41.	200 x 200 x 5mm white glazed ceramic wall tiles to :Walls	6.00	m <sup>2</sup>		
42.	Soap, dishes, toilet roll holders ETC Standard white glazed semi recessed toilet roll holder with ashtray size 150 x 150mm	9.00	No		
<b>Plumbing and drainage: Sanitary Fittings</b>					
43.	Stainless steel. Wall hung bowl urinal complete with spreader, 40mm waste outlet and domical grating fixed to walls	3.00	No		
44.	White vitreous china glazed fireclay .Basin size 510 x 405 mm with two tapholes bolted to walls	6.00	No		
45.	Low level w.c. suite comprising was down pan, matching 9 litres low level cistern with lid and fitments, flush pipe and heavy duty double flap and seat fixed to wall and floor	9.00	No		
<b>Traps ETC</b>					
46.	uPVC. 40mm Bottle trap including tailpipe and wall flange	6.00	No		
<b>Taps, Valves ETC</b>					
47.	Chrome plated brass tap and sundries. 15mm Angle regulating	17.00	No		



	valve with stainless steel braided connector pipe 315mm girth with chromium plated connectors both ends vent as required				
48.	Chrome plated brass tap and sundries. 15mm Raised nose pillar tap	6.00	No		
<b><u>Water supply pipes</u></b>					
49.	Class 12 HPE type IV water pipes including all straight joints and connectors laid in ground in trenches not less than 600mm deep including excavations, backfilling etc. 25mm Pipes laid in ground in trenches	50.00	m		
50.	Hard drawn thin walled class 0 copper to SABS 460 including all straight joints and connectors 15 mm pipe fixed or chased into walls.	36.00	m		
51.	Extra over class 0 copper pipes for brass capillary fittings 15 mm fittings (elbows, tees, reducing tees, adaptors couplings, etc.)	42.00	No		
<b><u>Internal soil, waste and vent piping</u></b>					
52.	uPVC soil, waste and vent pipes including all straight joints and connectors. 40 mm pipes laid in ground under soli floors.	12.00	m		
53.	Extra over iPVC pipes for fittings .40 mm bend	9.00	No		
54.	Extra over iPVC pipes for fittings .110mm Access bend	9.00	No		
55.	Extra over iPVC pipes for fittings .110 mm Access bend with vent horn	8.00	No		
56.	Extra over iPVC pipes for fittings .40 mm plain junction	2.00	No		
57.	Extra over iPVC pipes for fittings .110 mm access junction	4.00	No		
58.	Extra over iPVC pipes for fittings .110 mm access reducing junction	4.00	No		
59.	Extra over iPVC pipes for fittings .50mm two-way vent valve	6.00	No		

<b>Drainage</b>					
60.	Underground twin-wall uPVC structured wall pipes laid in ground, including excavations backfilling, etc. and all straight joints between pipes. 110 mm pipes laid in and including trenches exceeding 2m and not exceeding 3m deep	1.00	m		Rates only
61.	Extra over for the following fittings to underground twin-wall pipes. 110mm Rodding eye	2.00	No		
62.	Inspection chambers. Excavate for and build inspection chamber size 900mm x 600mm internally and exceeding 500mm and not exceeding 1000mm deep to invert	1.00	No		Rates only
63.	Cast iron gratings, covers etc..900 x 900mm Single seal manhole cover and frame type (171kg)	3.00	No		
<b>Glazing: Glazing to steel with putty</b>					
64.	4mm clear float glass. Panes not exceeding 0.1m <sup>2</sup>	7.00	m <sup>2</sup>		
<b>Mirrors etc.</b>					
65.	4mm silver float glass copper backed mirrors with polished edges fixed to walls with double sided adhesive tape. Mirror size 450 x 600mm high	6.00	No		
<b>External works : Road works, pavings, walkways, etc.</b>					
66.	Interlocking paving road stones type SF 35MPa laid on and including 20mm clean sand bed to falls and currents, including all cutting and waste. 80mm Interlocking road stones in paving in road, pavings etc.	6.00	m <sup>2</sup>		
<b>Paintwork</b>					
<b>On new plastered or screeded surface</b>					

<b>One coat alkali-resistant plaster primer and two coats acylic PVA paint</b>					
67.	On external smooth plastered walls	129.00	m <sup>2</sup>		
<b>One coat alkali resistant plaster primer, one coat undercoat and two coats eggshell enamel paint</b>					
68.	On internal smooth plastered walls and columns	135.00	m <sup>2</sup>		
<b>On metal</b>					
<b>Touch up factory primer and one coat undercoat and two coats gloss enamel paint</b>					
69.	On windows with burglar bars (both sides measured flat)	10.00	m <sup>2</sup>		
70.	On flush panel doors and frames (both sides measured flat)	65.00	m <sup>2</sup>		
<b>Wash with metal conditioner and two coats Acrylic PVA paint</b>					
71.	On underside of profiled roof sheeting and ceilings (measured on flat to ceiling area)	60.00	m <sup>2</sup>		
<b>Electrical wiring of the ablution block</b>					
<b>General repairs_ : Ordinary excavations, fillings, etc</b>					
72.	Extra over trench and hole excavations in earth for excavation in :Trenches and holes	20.00	m <sup>3</sup>		
73.	Earth filling obtained from the excavations and/ or prescribed stock piles on site compacted to 93% mod aashto density .Backfilling to trenches, holes, etc	20.00	No		
<b>General repairs: Ordinary excavations, fillings, etc</b>					
74.	Extra over trench and hole excavations in earth for excavation in : Trenches and holes	20.00	m <sup>3</sup>		
75.	Earth filling obtained from the excations and / or prescribed stock piles on site compacted to 93% mod aashto density. Backfilling to trenches, holes etc	20.00	No.		
<b>Chasing in brick walls (pipes, etc, elsewhere measured)</b>					

76.	Chasing in of galvanised/pvc pipes, channels trunking, etc in a straight line. 0.L.9000 Galvanised trunking	15.00	m		
<b>Low tension distribution</b>					
77.	Cast in concrete, surface and or screed .20mm Diameter	80.00	m		
<b>Rigid pvc conduit</b>					
78.	Cast in concrete, surface bed of screed. 20mm Diameter	80.00	m		
79.	Pvc wire 4mm <sup>2</sup>	80.00	m		
80.	Underground cable pvc, swa PVC Installed .2 core 10mm <sup>2</sup>	30.00	m		
81.	Cable termination of the following cables .2 Core 10mm <sup>2</sup>	2.00	No		
82.	16Amp Switches .Single Lever industrial type surface mounted	2.00	No		
83.	Daylight switches .10 Amp including mounting bracket surface mounted as national or other equal or approved.	1.00	No		
84.	PVC surface "PGA" boxes .100 x 100mm	10.00	No		
85.	Draw boxes miscellaneous junctions 60mm Diameter PVC	10.00	No		
86.	Single pole .1-10 Amp	2.00	No		
87.	Single pole .30-40 Amp	1.00	No		
88.	Oval spherical bowl fitting gallery only scwneck 110mm diameter .Ceiling porcelain	9.00	No		
89.	Round bulk head fitting with whit reflector and clear polycarbonate similar or equal to "UNILUX 7610".With lamp holder-100w B5 fitting complete	2.00	No		
90.	Surface mounted fluorescent fitting complete with tube and prismatic diffuser similar or equal to "Lascon M6".2 × 58W	2.00	No		

**Replace “Yorkshire” fuss or circuit breaker with “New Pole” type circuit breaker and drip-roof bow**

91.	<u>Earthing and bonding</u> .Earthing of metal roof with 50mm <sup>2</sup> copper wire in 25mm conduit connected to 1,5mm earth spike metre	1.00	No		
<b>Including fastening of cable into standard municipal wooden pole by stainless steel strapping, wire clamps to O,H wire and trenching shall be EXCLUDED</b>					
92.	Meter boards, distribution boards and supply mains .Indoor distribution board flush “SKO”	1.00	No		
93.	<u>Pedestal trunking. Labelling of single phase distribution boards</u>	1.00	No		

**Subtotal**

**Preliminary 8%**

**Contingency 10%**

**VAT @        %**

**Total**

*Enter 0% VAT rate if not VAT registered.*

*\* Columns A to D to be completed as applicable by Public Entity*

**GRAND TOTAL FOR LOT 1**

**N\$.....**

**Priced Activity Schedule Authorised By:**

Name:		Signature:	
Position:		Date:	
Authorised for and on behalf of:	Company		

**LOT 2: OTJITOKO PRIMARY SCHOOL****EARTH WORK**

Item No	Brief Description of Services	Quantity	Unit of Measure	Unit Price	Total Price
A*	B*	C*	D*	E	F
<b>Bulk excavations, fillings, etc</b>					
1.	Extra over bulk excavation in earth for excavation in Soft rock (the use of jack hammers is necessary.	15.00	m <sup>3</sup>		
2.	Extra over bulk excavation in earth for excavation in Hard rocks (blasting is necessary	15.00	m <sup>3</sup>		
3.	Extra over all excavations for carting Surplus material from excavations and/or stock piles on site to a dumping site to be located by the contractor	50.00	m <sup>3</sup>		
<b>Ordinary excavations, fillings</b>					
4.	Earth filling obtained from the excavations and/or prescribed stock piles on site compacted to 93% mod AASHTO density Backfilling to trenches, holes, etc.	13.00	m <sup>3</sup>		
5.	Earth filling supplied by the contractors to 93% mod AASHTO density Under floors, steps, pavings, etc.	75.00	m <sup>3</sup>		
6.	Compaction of filling Extra over all filling compacted to 93% mod AASHTO fir compacting to 98% AASHTO	78.00	m <sup>3</sup>		
7.	Coarse river and sand filling supplied by the contractor Backfilling behind retaining walls	26.00	m <sup>3</sup>		
8.	Soil poisoning. Soil insecticide under floors, paving, etc. including forming and poisoning shallow furrows and ramming	84.00	m <sup>2</sup>		
9.	Soil poisoning .Soil insecticide to bottoms of trenches, holes, etc.	65.00	m <sup>2</sup>		
<b>Concrete, Formwork and Reinforcement</b>					

10.	<u>Concrete work (unreinforced and reinforced) 15Mpa/ 19mm concrete</u> .Surface beds, aprons, pavings, ramps, etc. cast in panels	5.00	m <sup>3</sup>		
11.	25Mpa/ 19mm concrete Footings, bases and ground beams	10.00	m <sup>3</sup>		
12.	25Mpa/ 19mm concrete Surface beds, aprons, pavings, ramps, etc. cast in panels	12.00	m <sup>3</sup>		
<b>Masonry: Brickwork in foundation</b>					
13.	Brickwork of 7MPa cement bricks in Class 1 mortar. Half brick wall	15.00	m <sup>2</sup>		
14.	Brickwork of 14MPa cement bricks in class 1 mortar. One brick wall	30.00	m <sup>2</sup>		
<b>Brickwork in superstructures</b>					
15.	Brickwork of 7MPa cement bricks in Class 1 mortar. Half brick wall	40.00	m <sup>2</sup>		
16.	Brickwork of 7MPa cement bricks in Class 1 mortar. One brick wall	130.00	m <sup>2</sup>		
<b>Brickwork sundries</b>					
17.	Galvanised hoop iron ties.1.6mm Galvanised hoop iron tie 30mm wide and 750 mm girth build into brickwork and wrapped around and spiked to wall plate	6.00	No		
18.	Prestressed prefabricated lintels 105 X 75mm Lintels in lengths not exceeding 3m	12.00	m		
<b>Waterproofing: Damp-proofing of walls and floors</b>					
19.	One layer of approved 375 micron embossed damp proof course. In walls (110mm and 22mm wide)	60.00	m <sup>2</sup>		
20.	One layer of approved 250 micron under surface bed type waterproof sheeting sealed at laps with pressure sensitive tap Under	78.00	m <sup>2</sup>		

	surface beds, apron. etc				
<b>Roof coverings: 0.5mm Galvanised corrugated iron (Z275 spelter) roof sheeting with 0.6mm galvanised sheet steel accessories fixed in strict accordance with the manufacturer's instructions</b>					
21.	0.58mm "IBR" profile full hard galvanised (Z275 spelter) steel troughed roofing with 0.8mm galvanised sheet steel accessories fixed in strict accordance with the manufacturer's instruction. Roof sheeting in single lengths sheet	80.00	m <sup>2</sup>		
22.	0.5mm 'IBR 686' Aluzinc profile steel toughed roofing and all accessories fixed in strict accordance with the manufacturer's Instructions with fastening brackets and fixing specifications for areas of strong winds according to : Clotan Steel" with all exposed roofing screws, bolts, etc. sealed with a suitable acrylic waterproofing system .Ridge capping	12.00	m		
<b>Roof and wall insulation</b>					
23.	4mm 'Alucushion" bubble oil insulation with aluminium foil one side and white polyethylene other side or other equal and approved. Insulation laid taut over purlins and fixed concurrent with roof covering and vertical cladding including galvanise steel straining wires.	72.00	m <sup>2</sup>		
<b>Carpentry Work: Flush Doors</b>					
24.	40mm Semi-solid flush doors with hardboard covering both sides and concealed hardwood edge strips. Door size 813 X 2032mm high	7.00	No		
<b>Ceilings and partitions: Metal ceilings</b>					



25.	0.5mm IBR profile full hard galvanised steel troughed roofing with 0.8mm galvanised sheet steel accessories fixed in strict accordance with the manufacturer's instructions. Ceilings in single length sheets fixed horizontally to underside of steel purlins	78.00	m <sup>2</sup>		
26.	0.5mm IBR profile full hard galvanised steel troughed roofing with 0.8mm galvanised sheet steel accessories fixed in strict accordance with the manufacturer's instructions .Extra over ceiling for trap door size 600x600mm, the opening formed of 40x40x0.8mm galvanised sheet metal angle from all round mitred and pop-riveted to profiled metal ceiling and 50 x 50 x 3mm mild steel angle frame all round mitred and welded together and to steel bracing, the trap door formed of IBR profiled metal sheeting with 40 x 40 x 0.8mm galvanised sheet metal angle frame all round mitred and pop-riveted to profiled metal ceiling	1.00	No		
<b>Floor Covering, wall linings etc. <u>Floor coverings</u></b>					
27.	300 x 300 x 2mm fully flexible vinyl tiles to patterns in differing colours fixed with adhesive recommended by and laid in strict accordance with the manufacturer's instructions. Floors	87.00	m <sup>2</sup>		
<b>Ironmongery</b>					
28.	Door and window sundries .Silver anodised aluminium door stop with rubber buffer fixed to floor	12.00	No		
<b>Structural steelwork: Steel trusses etc.</b>					
29.	Welded roof trussers of angle section hollow section rafters, rails, struts, braces, cleats etc. and flat section barer, gusset and connection plates bolted to	550.00	kg		

	concrete. Truss exceeding 6m and not exceeding 8m span				
30.	Base plates, angles and bolts to trusses .Base or anchor plates	55.00	kg		
31.	Base plates, angles and bolts to trusses.12mm U-shaped anchor bolt 750mm girth cast into top of concrete	12.00	No		
<b>Purlins, girts, bracing etc.</b>					
32.	Purlins and braces bolted to steel Lipped channel section purlins	432.00	kg		
33.	Purlins and braces bolted to steel Lipped channel section ceiling rails	410.00	kg		
<b>Metal work :Mild steel windows and doors</b>					
34.	Residential type window with horizontal bars with solid brass or chromium plated fittings and fitted with and including type NBP33 burglar bars to the opening sections only. Window type C2H size 1022 x 654mm high	6.00	No		
<b>Pressed steel door frames</b>					
35.	1.2mm Double rebated frames suitable for half brick walls Frame for door size 813 x 2032mm high	7.00	No		
<b>Pressed steel combination doors and frames</b>					
36.	Combination single panel chawl type doors with 14.2mm rebated door rebate door frames to suit one brick walls .Frame with door size 813 x 2032mm high with palatch	3.00	No		
37.	Combination single panel chawl type doors with 14.2mm rebated door rebate door frames to suit one brick walls .Frame with door size 813 x 2032mm high with three level lockset and chromium plated furniture.	2.00	No		

<b>Plastering: External Plaster</b>					
38.	One coat cement plaster wood floated smooth on brick work to: Walls	120.00	m <sup>2</sup>		
<b>Internal plaster</b>					
39.	One coat compo plaster steel trowelled smooth on brickwork to: Walls	180.00	m <sup>2</sup>		
<b>Dividing strip, water bars, cornee protectors, etc</b>					
40.	Mild steel. 50 x 50 x 5mm angle section edge protector in lengths with and including 2 x 25mm flat section bent lugs each 200mm girth welded on at maximum 300mm centres including embedding in concrete	19.00	m		
<b>Tiling :Wall tiling</b>					
41.	200 x 200 x 5mm white glazed ceramic wall tiles to :Walls	6.00	m <sup>2</sup>		
42.	Soap, dishes, toilet roll holders ETC Standard white glazed semi recessed toilet roll holder with ashtray size 150 x 150mm	9.00	No		
<b>Plumbing and drainage: Sanitary Fittings</b>					
43.	Stainless steel. Wall hung bowl urinal complete with spreader, 40mm waste outlet and domical grating fixed to walls	3. 00	No		
44.	White vitreous china glazed fireclay .Basin size 510 x 405 mm with two tapholes bolted to walls	6.00	No		
45.	Low level w.c. suite comprising was down pan, matching 9 litres low level cistern with lid and fitments, flush pipe and heavy duty double flap and seat fixed to wall and floor	9.00	No		
<b>Traps ETC</b>					
46.	uPVC. 40mm Bottle trap including tailpipe and wall flange	6.00	No		
<b>Taps, Valves ETC</b>					

47.	Chrome plated brass tap and sundries. 15mm Angle regulating valve with stainless steel braided connector pipe 315mm girth with chromium plated connectors both ends vent as required	17.00	No		
48.	Chrome plated brass tap and sundries. 15mm Raised nose pillar tap	6.00	No		
<b><u>Water supply pipes</u></b>					
49.	Class 12 HPE type IV water pipes including all straight joints and connectors laid in ground in trenches not less than 600mm deep including excavations, backfilling etc. 25mm Pipes laid in ground in trenches	50.00	m		
50.	Hard drawn thin walled class 0 copper to SABS 460 including all straight joints and connectors 15 mm pipe fixed or chased into walls.	36.00	m		
51.	Extra over class 0 copper pipes for brass capillary fittings 15 mm fittings (elbows, tees, reducing tees, adaptors couplings, etc.)	42.00	No		
<b><u>Internal soil, waste and vent piping</u></b>					
52.	uPVC soil, waste and vent pipes including all straight joints and connectors. 40 mm pipes laid in ground under soli floors.	12.00	m		
53.	Extra over iPVC pipes for fittings .40 mm bend	9.00	No		
54.	Extra over iPVC pipes for fittings .110mm Access bend	9.00	No		
55.	Extra over iPVC pipes for fittings .110 mm Access bend with vent horn	8.00	No		
56.	Extra over iPVC pipes for fittings .40 mm plain junction	2.00	No		
57.	Extra over iPVC pipes for fittings .110 mm access junction	4.00	No		
58.	Extra over iPVC pipes for fittings .110 mm access reducing junction	4.00	No		
59.	Extra over iPVC pipes for fittings .50mm two-way vent valve	6.00	No		

<b>Drainage</b>					
60.	Underground twin-wall uPVC structured wall pipes laid in ground, including excavations backfilling, etc. and all straight joints between pipes. 110 mm pipes laid in and including trenches exceeding 2m and not exceeding 3m deep	1.00	m		Rates only
61.	Extra over for the following fittings to underground twin-wall pipes. 110mm Rodding eye	2.00	No		
62.	Inspection chambers. Excavate for and build inspection chamber size 900mm x 600mm internally and exceeding 500mm and not exceeding 1000mm deep to invert	1.00	No		Rates only
63.	Cast iron gratings, covers etc.. 900 x 900mm Single seal manhole cover and frame type (171kg)	3.00	No		
64.	Septic Tanks. Excavate for and build septic tank size 6110 x 2960mm internally and 2220mm deep to invert with internal one brick division wall with five 110mm uPVC Pipes 00mm long built through wall, five 110mm uPVC plain junctions each with a 450mm length of 110mm uPVC pipe and two 600 x 900mm access manhole in top slab	1.00	No		
<b>Glazing: Glazing to steel with putty</b>					
65.	4mm clear float glass. Panes not exceeding 0.1m <sup>2</sup>	7.00	m <sup>2</sup>		
<b>Mirrors etc.</b>					
66.	4mm silver float glass copper backed mirrors with polished edges fixed to walls with double sided adhesive tape. Mirror size 450 x 600mm high	6.00	No		

<b>External works : Road works, pavings, walkways, etc.</b>					
67.	Interlocking paving road stones type SF 35MPa laid on and including 20mm clean sand bed to falls and currents, including all cutting and waste. 80mm Interlocking road stones in paving in road, pavings etc.	6.00	m <sup>2</sup>		
<b>Paintwork</b>					
<b>On new plastered or screeded surface</b>					
<b>One coat alkali-resistant plaster primer and two coats acylic PVA paint</b>					
68.	On external smooth plastered walls	129.00	m <sup>2</sup>		
<b>One coat alkali resistant plaster primer, one coat undercoat and two coats eggshell enamel paint</b>					
69.	On internal smooth plastered walls and columns	135.00	m <sup>2</sup>		
<b>On metal</b>					
<b>Touch up factory primer and one coat undercoat and two coats gloss enamel paint</b>					
70.	On windows with burglar bars (both sides measured flat)	10.00	m <sup>2</sup>		
71.	On flush panel doors and frames (both sides measured flat)	65.00	m <sup>2</sup>		
<b>Wash with metal conditioner and two coats Acrylic PVA paint</b>					
72.	On underside of profiled roof sheeting and ceilings (measured on flat to ceiling area)	60.00	m <sup>2</sup>		
<b>Electrical wiring of the ablution block</b>					
<b>General repairs : Ordinary excavations, fillings, etc</b>					
73.	Extra over trench and hole excavations in earth for excavation in :Trenches and holes	20.00	m <sup>3</sup>		
74.	Earth filling obtained from the excavations and/ or prescribed stock piles on site compacted to 93% mod aashto density .Backfilling to trenches, holes, etc	20.00	No		

<b>General repairs: Ordinary excavations, fillings, etc</b>					
75.	Extra over trench and hole excavations in earth for excavation in : Trenches and holes	20.00	m <sup>3</sup>		
76.	Earth filling obtained from the excations and / or prescribed stock piles on site compacted to 93% mod aashto density. Backfilling to trenches, holes etc	20.00	No.		
<b>Chasing in brick walls (pipes, etc, elsewhere measured)</b>					
77.	Chasing in of galvanised/pvc pipes, channels trunking, etc in a straight line. O.L.9000 Galvanised trunking	15.00	m		
<b>Low tension distribution</b>					
78.	Cast in concrete, surface and or screed .20mm Diameter	80.00	m		
<b>Rigid pvc conduit</b>					
79.	Cast in concrete, surface bed of screed. 20mm Diameter	80.00	m		
80.	Pvc wire 4mm <sup>2</sup>	80.00	m		
81.	Underground cable pvc, swa PVC Installed .2 core 10mm <sup>2</sup>	30.00	m		
82.	Cable termination of the following cables .2 Core 10mm <sup>2</sup>	2.00	No		
83.	16Amp Switches .Single Lever industrial type surface mounted	2.00	No		
84.	Daylight switches .10 Amp including mounting bracket surface mounted as national or other equal or approved.	1.00	No		
85.	PVC surface "PGA" boxes .100 x 100mm	10.00	No		
86.	Draw boxes miscellaneous junctions 60mm Diameter PVC	10.00	No		
87.	Single pole .1-10 Amp	2.00	No		

88.	Single pole .30-40 Amp	1.00	No		
89.	Oval spherical bowl fitting gallery only scewneck 110mm diameter .Ceiling porcelain	9.00	No		
90.	Round bulk head fitting with whit reflector and clear polycarbonate similar or equal to "UNILUX 7610".With lamp holder-100w B5 fitting complete	2.00	No		
91	Surface mounted fluorescent fitting complete with tube and prismatic diffuser similar or equal to "Lascon M6".2 × 58W	2.00	No		
<b>Replace "Yorkshire" fuss or circuit breaker with "New Pole" type circuit breaker and drip-roof bow</b>					
92.	<u>Earthing and bonding</u> .Earthing of metal roof with 50mm <sup>2</sup> copper wire in 25mm conduit connected to 1,5mm earth spike metre	1.00	No		
<b>Including fastening of cable into standard municipal wooden pole by stainless steel strapping, wire clamps to O,H wire and trenching shall be EXCLUDED</b>					
93.	Meter boards, distribution boards and supply mains .Indoor distribution board flush "SKO"	1.00	No		
94.	<u>Pedestal trunking. Labelling of single phase distribution boards</u>	1.00	No		
				<b>Subtotal</b>	
				<b>Preliminary 8%</b>	
				<b>Contingency 10%</b>	
				<b>VAT @      %</b>	
				<b>Total</b>	

*Enter 0% VAT rate if not VAT registered.*

\* Columns A to D to be completed as applicable by Public Entity

**GRAND TOTAL FOR LOT 2**

**N\$.....**

**Priced Activity Schedule Authorised By:**

Name:		Signature:	
Position:		Date:	
Authorised for and on behalf of:	Company		



## SECTION V: SPECIFICATIONS AND COMPLIANCE SHEET

Procurement Reference Number: \_\_\_\_\_

## SECTION VI: GENERAL CONDITIONS OF CONTRACT AND CONTRACT AGREEMENT

Any resulting contract shall be placed by means of a Purchase Order/Letter of Acceptance and shall be subject to the General Conditions of Contract (GCC) for the Procurement of Goods (Ref. **G/RFQ-WCC**) (available at public entities physical address/website: Insert Public Entity address/website) except where modified by the Special Conditions below.

## SECTION VII: CONTRACT AGREEMENT

Any resulting contract shall be placed by means of a Purchase Order/Letter of Acceptance and shall be subject to the General Conditions of Contract (GCC) for the Procurement of Works except where modified by the Special Conditions below.

## SECTION VIII SPECIAL CONDITIONS OF CONTRACT

Procurement Reference Number: .....

The clause numbers given in the first column correspond to the relevant clause number of the General Conditions of Contract. *[This section is to be customised by the Public Entity to suit the requirements of the specific procurement].*

GCC Clause Reference	Special Conditions
<b>Project Manager</b> GCC 1.1(y)	The Project Manager is: Kunene Regional Council: Directorate of Education, Arts and Culture
<b>Site</b> GCC 1.1(aa)	Versteende Woud Primary School and Otjitoko Primary School.
<b>Start Date</b> GCC 1.1(dd)	The Start Date shall be: 7 days after issuing of Purchase Order.
<b>The Works</b> GCC 1.1(h)	The Works consist of: Construction and electrification of new ablution block
<b>Language and Law</b> GCC 3.1	The language of the contract is English The law that applies to the Contract is the law of Namibia.
<b>Project</b>	The Project Manager shall obtain specific approval from the Employer before carrying out any of his duties under the Contract which in the

GCC Clause Reference	Special Conditions
<b>Manager's Decisions 4.1</b>	Project Manager's opinion will cause the amount finally due under the Contract to exceed the Contract Price or will give entitlement to extension of time. This requirement shall be waived in an emergency affecting safety of personnel or the Works or adjacent property.
<b>Notices GCC 6</b>	<p>Any notice shall be sent to the following addresses:</p> <p>For the Employer, the address shall be as given on the page 2 of this Bidding Document and the contact name shall be:</p> <p>Kunene Regional Council Procurement Management Unit Mbumbijazo Muharukua Street P/Bag 502, Opuwo 065-273 950 <b>Email: pmu.kunenerc@gmail.com</b></p> <p>For the Contractor, the address shall be as given on the first page of the Purchase Order/Letter of Acceptance and the contact name shall be</p>
<b>Insurance GCC 13.1</b>	<p>Except for the cover mentioned in (d)(i) hereunder, the other insurance covers shall be in the joint names of the Contractor and the Employer and the minimum insurance amounts shall be:</p> <ul style="list-style-type: none"> <li>(a) for the Works, Plant and Materials: (for the full amount of the works including removal of debris, professional fee etc...)</li> <li>(b) for loss or damage to Equipment: (for the replacement value of the equipment that the contractor intends to use on site until the taking over by the Employer.</li> <li>(c) for loss or damage to property (except the Works, Plant, Materials, and Equipment) in connection with Contract for an amount representing the value of the properties that are exposed to the action of the contractor in the execution of the works. It will extend to the property of the Procuring Entity as well).</li> <li>(d) for personal injury or death: <ul style="list-style-type: none"> <li>(i) of the Contractor's employees: [The Contractor shall</li> </ul> </li> </ul>

GCC Clause Reference	Special Conditions
	<p>take an adequate insurance cover for its employees for any claim arising in the execution of the works].</p> <p>(ii) of other people: [This cover shall be for an adequate amount for Third Party extended to the Employer and its representatives].</p> <p>(e) for loss or damage to materials on-site and for which payment have been included in the Interim Payment Certificate, where applicable.</p> <p>The Contractor shall choose to take the insurance covers indicated above as separate covers or a combination of the Contractor's All Risks coupled with the Employer's liability and First Loss Burglary, after approval of the Employer. All insurance covers shall be of nil or the minimum possible deductibles at sole expense of the contractor.</p>
<b>Intended Completion Date</b> GCC 16.1	The Intended Completion Date for the whole of the Works shall be: 60 days from date of site handover.
<b>Possession of the Site</b> GCC 20.1	The Site Possession Date shall be: 7 days after issuing of Purchase Order
<b>Procedure for Disputes</b> GCC 24	No Adjudicator shall be appointed under the contract and arbitration shall not apply. If any dispute arises between the Employer and the Contractor in connection with or arising out of the Contract, the parties shall seek to resolve any such dispute by amicable agreement. If the parties fail to resolve such dispute by amicable agreement, within 14 days after one party has notified the other in writing of the dispute, then the dispute shall be referred to court by either party.
<b>Program</b> GCC 25.1	The Contractor shall submit for approval a Program for the Works within 7 working days from the date of the Letter of Acceptance or issue of Purchase Order Agreement.
<b>GCC 25.3</b>	Program updates shall be required.
<b>Defects Liability Period</b> GCC 33.1	The Defects Liability Period is: 365 days after final inspection and handover.
<b>Payment Certificates</b> GCC 39.7	“ A single statement of the estimated value of the work executed shall be submitted on completion of the Works. The Project Manager shall check the statement and certify the amount to be paid to the Contractor”.

GCC Clause Reference	Special Conditions
<b>Payments</b> <b>GCC 40</b>	The amount certified by the Project Manager shall be paid in full within 30 days of receipt by the Employer of an invoice, supported by: (a) the payment certificate; and (b) a certificate of Completion of the Works.
<b>Adverse weather Conditions</b> <b>GCC 41.1 (I)</b>	<i>Weather condition under which normal project work cannot be executed.</i>
<b>Price Adjustment</b> <b>GCC 44.</b>	The Contract is not subject to price adjustment.
<b>Retention</b> <b>GCC 45.</b>	10% of the amount shall be retained from any payment. Half of the retention money will be released after formal taking over of the Works and the remaining shall be released after the Defect Liability Period subject to the Contractor making good all defects.
<b>Liquidated Damages</b> <b>GCC 46.1</b>	The liquidated damages for the whole of the Works are 4% per week.  The maximum amount of liquidated damages for the whole of the Works is amount based on a maximum number of weeks 10% maximum of contract price.
<b>Advance Payment</b> <b>GCC 48.1</b>	No advance payment shall be made
<b>Performance Security</b> <b>GCC 49.1</b>	Performance Security of 10%. N/A
<b>GCC 56.1</b>	Operating and maintenance manuals should be supplied to the employer by the contractor not later than: Provided during hand over.
<b>GCC 59.1</b>	The percentage to apply to the value of the work not completed, representing the Employer's additional cost for completing the Works, is: 10% of the contracted amount

### SCHEDULE 3: QUOTATION CHECKLIST SCHEDULE

**Procurement Reference No.:**

<b>Description</b>	<b>Attached</b>	<b>Not Attached</b>
Quotation letter		
Priced Activity Schedules		
Specification and Compliance Sheet		
Bid Declaration Security		
Valid certified Company registration Certificate		
Reference letter from Kunene Regional Constituency Councillor		
Valid certified Affirmative Action Compliance Certificate		
Valid certified Good Standing Certificate from Social Security		
Valid certified Good Standing Certificate from Ministry of Finance		
Valid certified SME Certificate		
Confirmation of Bank Account Letter from a Commercial Bank		
Reference letters		
Qualification of a Plumber, Brick Layer from reputable education institution accredited by NQA		
Qualification of Electrician from a reputable education institution accredited by NQA with wiring licence.		

**Disclaimer:** The list defined above is meant to assist the Bidder in submitting the relevant documents and shall not be a ground for the bidder to justify its non-submission of major documents for its quotation to be responsive. The onus remains on the Bidder to ascertain that it

*has submitted all the documents that have been requested and are needed for its submission to be complete and responsive.*